

July 2011



Class Specification 26.00 cc Sedan Updated July 2011

1. Appearance- Speedway Sedan
2. Engine - Zenoah G2D70 / G230RC/ G240RC / G260RC / G270RC / SIKKTOY23
3. Fitment of 25.4 kits allowed.
4. No other modifications allowed. - Tuned pipes can be used.
5. Carby can be rotated.
6. No reed valve engines allowed.
7. Dimensions - Wheelbase 24-26 inches (max)
 - Width 20 inch track (max)
 - Length 48 inches incl. spoiler
8. Weight - no minimum for this class
9. Wings -no higher than roofline
 - Side Dams - no higher than roofline.
10. Wheels - 4.5 inches max width
- 11.Suspension Front – Beam or Independent
 - Rear – Solid Rear Axle
- 12.Frame - Steel Tube only
- 13.Driveline - Belt / Chain/ Victa diff/ Quick change must be locked
 - No multi speed gearboxes allowed
- 14.Brakes - All racecars must have an operational brake at all times
- 15.Clutch -mandatory standard 2 shoe clutch as supplied by the Engine Manufacturer
- 16.Fuel - unleaded/premium unleaded with oil additive only.
- 17.Must have kill switch indicated by blue triangle on body
- 18.Transponder to be fitted behind front axle

July 2011