

July 2011



Class Specification 26.00 cc Sprintcar Updated July 2011

1. Appearance - Must resemble a full size Sprintcar.
2. Engine - Zenoah G2D70/ G230RC/ G260RC/ G270RC /SIKKTOY23
 - Fitment of 25.4 kits allowed.
 - No other modifications allowed.
 - Tuned pipes can be used.
 - Carby can be rotated.
 - No reed valve engines allowed.
3. Dimensions - wheelbase 24 inches (max)
 - Width 20 inches (max)
 - Length 39 Inches (max)
 - Chassis height Min 11 ½ inches up to Max 15 ¾ inches
4. Weight - no minimum for this class.
5. Wings - Top 15 inches wide
 - Side 18 inches long and 7 1/2 inches high.
 - Front 9 inches x 6 ½ inches with 3 inch sides

MUST NOT EXCEED
6. Wheels - Tyre width Open, rim width 4 ½ inches
7. Suspension - No independent allowed.
8. Frame - Steel Tube Only.
9. Driveline - Belt / Chain / Victa diff / Quick change must be locked
 - No multi speed gearboxes allowed
10. Brakes - All racecars must have an operational brake at all times
11. Clutch - mandatory standard 2 shoe clutch as supplied by the Engine Manufacturer
12. Fuel - Unleaded / premium unleaded with oil additive only.
13. Kill Switch - Must be fitted and mounted on top RHR of roll cage
14. Transponder must be fitted behind front axle