



## Class Specification 26.00 cc Sedan

- 1/ Appearance- Speedway Sedan
- 2/ Engine - Zenoah G2D70 / G230RC/ G240RC / G260RC / G270RC / SIKKTOY23
  - Fitment of 25.4 kits allowed.
  - No other modifications allowed. - Tuned pipes can be used.
  - Carby can be rotated.
  - No reed valve engines allowed.
- 3/ Dimensions
  - Wheelbase 24-26 inches (max)
  - Width 20 inch track (max)
  - Length 48 inches incl. spoiler
- 4/ Weight - no minimum for this class.
- 5/ Wings
  - No higher than roofline
  - Side Dams - no higher than roofline.
- 6/ Wheels - 4.5 inches max width
- 7/ Suspension
  - Front – Beam or Independent
  - Rear – Solid Rear Axle
- 8/ Frame - Steel Tube only
- 9/ Driveline
  - Belt / Chain/ Victa diff/ Quick change must be locked
  - No multi speed gearboxes allowed
- 10/ Brakes - All racecars must have an operational brake at all times
- 11/ Clutch -mandatory standard 2 shoe clutch as supplied by the Engine Manufacturer
- 12/ Fuel - unleaded/premium unleaded with oil additive only.
- 13/ Must have kill switch indicated by blue triangle on body