



## Class Specification 26.00 cc Sprintcar

- 1/ Appearance - Must resemble a full size Sprintcar.
- 2/ Engine - Zenoah G2D70/ G230RC/ G260RC/ G270RC / SIKKTOY23  
- Fitment of 25.4 kits allowed.  
- No other modifications allowed.  
- Tuned pipes can be used.  
- Carby can be rotated.  
- No reed valve engines allowed.
- 3/ Dimensions - wheelbase 24 inches (max)  
- Width 20 inches (max)  
- Length 39 Inches (max)  
- Chassis height Min 11 ½ inches up to Max 15 ¾ inches
- 4/ Weight - no minimum for this class.
- 5/ Wings - Top 15 inches wide  
- Side 18 inches long and 7 1/2 inches high.  
- Front 9 inches x 6 ½ inches with 3 inch sides  
**MUST NOT EXCEED**
- 6/ Wheels - Tyre width Open, rim width 4 ½ inches
- 7/Suspension - No independent allowed.
- 8/ Frame - Steel Tube Only.
- 9/ Driveline - Belt / Chain / Victa diff / Quick change must be locked  
- No multi speed gearboxes allowed
- 10/ Brakes - All racecars must have an operational brake at all times
- 11/ Clutch - mandatory standard 2 shoe clutch as supplied by the Engine Manufacturer
- 12/ Fuel - Unleaded / premium unleaded with oil additive only.
- 13/ Kill Switch - Must be fitted and mounted on top RHR of roll cage